BERYL: 3.8m Stock Trailer - Data Sheet

Weight and Dimensions

Delivered Weight	~ 1100 kg
Maximum permitted weight	2000 kg
External Dimensions (L / W / H)	Body: 3800 / 2180 / 2100 mm Overall: 4800 / 2180 / 2500 mm
Internal Dimensions	3790 / 2170 / 1960 mm

Construction

Frame	Rolled steel
Body	Galvanised and painted
Stock Finishes	RAL 9001 (off-white);RAL 9005 (black); Stainless Steel
Insulation	5mm
Hitch and brake assembly	Alko hitch and Alko mechanical brakes

External Facilities

Electrical feeds	63 amp. Adapter cables included
Water inlet	Feed to onboard water tanks
Water storage	Twin 60 litre tanks: 1 X fresh water; 1 X waste
Pitch stability	4 X stability jacks
SIgnage and branding	Suitable for magnetic signage or decals; optional above hatch sign mount
Serving hatches	Single main serving hatch
Ventilation	Ventilation Window at front

Facilities (internal)

Electrical installation	63 amp consumer unit 8 X double sockets and 32 amp outlet for professional appliances
Pump	On board electric pump with automatic activation

Large utility sink	530 / 350 / 350 mm
Hand wash sink	400 / 380 / 300 mm
Water heater	2 kw X 15 litre water heater
Taps	Mixer tap and sensor tap for hand wash
Worktop	Stainless steel
Shelves	Stainless steel
Refrigeration	1 X double door 300 litre fridge suitable for GN1/1 trays Space for a further900 mm drinks fridge and a 600 mm fridge or freezer (not included in pricing)
Lighting	Recessed lighting in work area; illuminated service area; recessed lighting in serving hatches.
Gas box and pipework	Optional, not fitted on hire units
Extractor (where fitted)	1.9 mtr commercial extractor on prep side (not available on hire trailers)
Floor	Aluminium non-slip
Capacity (servers)	4

Safety, Regulatory and Certification

CoC	Rolling Stock holds Whole Vehicle Type Approval, EU and UK validity. All trailers sold with a Certificate of Conformity
Statutory plate	VIN plate displays VIN number and regulated data
Standards	CE mark affirms compliance with European standards
Electrical	All trailers tested by UK electricians and sold with EICR certificate
Gas	CP44 certificate (where gas is fitted)
Fire Safety	Optional fire blanket and Kidde extinguisher (types A, B, C)
Warranty	12 months parts and labour, subject to terms and conditions

Aftercare

Warranty	12 months parts and labour, most parts held in stock