Dorothy - Horsebox Style Bar and Catering Trailer

Data Sheet

Weight and Dimensions

Kerbside Weight	1300 kg
Max permissible weight	2180 kg
External Dimensions (L / W / H)	Body only: 2350 mm long or 3570 into the nose), 1700 mm wide, 2090 mm high Overall, including the hitch 4990 (long), width including wheels and mudguards 2360, overall height 2490 mm
Internal Dimensions	3520 long (into the nose) 1640 wide 1950 mm

Construction

Frame	Rolled steel
Body	Painted dark green RAL 6008
Insulation	5 mm
Hitch and brake assembly	Alko hitch and brakes

External Facilities

Electrical feeds	63 amp
Water storage	40 litre fresh and 40 litre waste water tanks
Pitch stability	2 X stability jacks at rear
Serving hatches	Three serving hatches
SIgnage and branding options	Above hatch fixed sign mounts and below hatch optional / removable sign mounts. Sign dimensions in mm (W / H) **Above the hatches** Main hatch: 1975 / 240 Front hatch: 1145 / 240 Rear hatch: 755 / 240 **Below the hatches** Main hatch: 1800 / 680 Front hatch: 1200 / 800 Rear hatch: 1400 / 600

Facilities (internal)

Interior lining	Easy clean powder coated sheet in cream
Electrical installation	63 amp consumer unit 8 X double sockets and 32 amp outlet for professional appliances
Pump	On board electric pump with automatic activation
Utility sink	300 X 300 mm
Handwash sink	250 X 250 mm
Taps	Mixer tap
Hot water	1.5 kw 10 litre electric water heater
Worktop	Hardwood, 2700 mm run, 600 mm deep on prep side; 450 mm on service side with 200 mm fold-out extension
Fold-out extensions	200 mm extensions to fold out when the hatch is open
Fold-up extension	450 mm fold-up extension at rear to extend worktop space
Shelves	Under counter stainless steel shelving
Refrigeration options	1 X sliding door 900 mm display drinks fridge Space for 1 X 600 mm fridge, or freezer
Lighting	Recessed lighting in work area, illuminated service area, recessed lighting in serving hatches.
Floor	Aluminium non-slip
Capacity (servers)	2-3

Safety, Regulatory and Certification

CoC	Rolling Stock holds Whole Vehicle Type Approval, EU and UK validity. All trailers sold with a Certificate of Conformity
Statutory plate	VIN plate displays VIN number and regulated data
Standards	CE mark affirms compliance with European standards
Electrical	All trailers tested by UK electricians and sold with EICR certificate
Gas	CP44 certificate (where gas is fitted)
Fire Safety	Optional fire blanket and Kidde extinguisher (types A, B, C)
Warranty	12 months parts and labour, subject to terms and conditions

Aftercare

Warranty	12 months parts and labour, most parts held in stock