GLADYS: Coffee, Bar and Light Catering Trailer

DATA SHEET

Weight and Dimensions

Delivered Weight	~ 670 kg
Maximum permitted weight	750 kg
External Dimensions (L / W / H)	Body: 2500 / 1920 / 2100 mm (L / W / H) Overall (including hitch): 3300 / 1920 / 2500 mm
Internal Dimensions	2490 / 1900 / 1960 mm

Construction

Frame	Rolled steel
Body	Stainless steel (airstream style) or sheet aluminium and painted
Insulation	5mm
Hitch and brake assembly	Standard hitch, unbraked

External

Electrical feeds	63 amp
Water storage	30 litre fresh and 30 litre waste water tanks
Pitch stability	4 X stability jacks
Stock Finishes	RAL 9001 (off-white);RAL 9005 (black); Stainless Steel
SIgnage and branding	Suitable for magnetic signage or decals; optional above hatch sign mount
Serving hatches	Single serving hatch
Ventilation	Ventilation Window at front

Facilities (internal)

Electrical installation	63 amp consumer unit 8 X double sockets and 32 amp outlet for professional appliances
Pump	On board electric pump with automatic activation
Utility sink	300 X 300 mm
Handwash sink	300 X 300 mm

Hot water	2 Kw 15 litre hot water heater
Taps	Mixer tap and sensor tap for hand wash
Worktop	Stainless steel - 620 mm deep on prep side; 450 mm on service side with fold out service ledge to make 650mm in total
Refrigeration	1 X double door 200 litre fridge suitable for GN1/1 trays
Lighting	Recessed lighting in work area; illuminated service area; recessed lighting in serving hatches.
Gas box and pipework	Optional, not fitted on hire units
Extractor (where fitted)	1 mtr commercial extractor on prep side (not available on hire trailers)
Floor	Aluminium non-slip
Capacity (servers)	1-2

Safety, Regulatory and Certification

CoC	Rolling Stock holds Whole Vehicle Type Approval, EU and UK validity. All trailers sold with a Certificate of Conformity
Statutory plate	VIN plate displays VIN number and regulated data
Standards	CE mark affirms compliance with European standards
Electrical	All trailers tested by UK electricians and sold with EICR certificate
Gas	CP44 certificate (where gas is fitted)
Fire Safety	Optional fire blanket and Kidde extinguisher (types A, B, C)
Warranty	12 months parts and labour, subject to terms and conditions

Aftercare

Warranty	12 months parts and labour, most parts held in stock